# MiaSolé 9X CIGS SOLAR CELL

## Thin Film CIGS Solar Cells: Powerful, Flexible, Lightweight

MiaSolé thin-film CIGS solar cells deposited on stainless steel substrates have high efficiency and provide significant advantages over conventional, rigid solar cells.

### **KEY FEATURES**

- ▶ Efficiency—Up to 16%
- ▶ Thin—0.33mm thick
- Lightweight—8.7g
- Configurable length
- Integration-ready for multiple product applications
- Innovative cell interconnect
- Flexible and shatter-proof
- Each cell identified by a unique barcode, providing comprehensive product genealogy

### PACKAGING, HANDLING AND STORAGE NOTES

- MiaSolé solar cells are sensitive to humidity and temperature. They must be stored at ≤10% relative humidity and between 10-35°C.
- Products made with MiaSolé solar cells require encapsulation to protect against moisture.
- Cells packaged in bundles of 150 units. Packages are resistant to moisture ingress.





### MiaSolé 9X CIGS SOLAR CELL

### NOMINAL PERFORMANCE BY 0.5% EFFICIENCY BINS<sup>‡</sup>


| Cell Efficiency       |                 |     | >14.0% | >14.5% | >15.0% | >15.5% | >16.0% |
|-----------------------|-----------------|-----|--------|--------|--------|--------|--------|
| Power                 | PMPP            | [W] | 1.95   | 2.02   | 2.08   | 2.15   | 2.20   |
| Maximum Power Voltage | V               | [V] | 0.524  | 0.537  | 0.541  | 0.546  | 0.552  |
| Maximum Power Current | I               | [A] | 3.73   | 3.77   | 3.84   | 3.93   | 3.98   |
| Open Circuit Voltage  | V <sub>oc</sub> | [V] | 0.651  | 0.663  | 0.667  | 0.671  | 0.676  |
| Short Circuit Current | J <sub>sc</sub> | [A] | 4.26   | 4.25   | 4.30   | 4.36   | 4.39   |

‡ Performance tested at Standard Test Conditions (STC). STC: 1000W/m<sup>2</sup>, AM1.5G, Cell Temperature 25C.

### PHYSICAL AND MECHANICAL SPECIFICATIONS

| Length                        | 308–315.5 mm                                |
|-------------------------------|---|
| Width: Cell Only              | 44.0 mm ± 0.25 mm                           |
| Width: Including Interconnect | 57.2 mm ± 0.25 mm                           |
| Thickness                     | 0.33 mm ± 0.1 mm                            |
| Weight                        | 8.7g ± 0.2g                                 |
| Cell Type                     | Thin Film CIGS on Stainless Steel Substrate |
| Packaging Info                | 150 cells per package, 10 packages per box  |

### **CELL DIAGRAM**





2590 Walsh Avenue, Santa Clara, California 95051, USA 1.408.919.5700 info@miasole.com www.miasole.com

MiaSolé and the MiaSolé logo are registered trademarks. © Jan 2019 MiaSolé. All rights reserved. Specifications included in this datasheet are subject to change without notice. MiaSolé Approved for Public Release. Part Number 302-189851-00-A